EcoFlow PowerPulse EV Charger (11.5kW)

Input & Output	Charge Power (configurable)	11.5 kW
	Rated Voltage	208/240 VAC
	Rated Current (configurable)	48 A
	Rated Frequency	60 Hz
	Residual Current Circuit Breaker (RCCB)	External RCCB required
	Input Cable Type	Pre-wired with: (L1, L2, Gnd)
	Input Cable Length	3.3 ft (1 m)
	Connector Type	SAE J1772
	Output Cable Length	24.6 ft (7.5 m)

Communication	Communication	Wi-Fi (2.4G), Bluetooth, RS485, CAN
	Authentication	EcoFlow App, Bluetooth
	Control & Monitoring	EcoFlow App, LCD Display
	Working Mode	Fast Charge, Scheduled Charge, Customized Charge, Smart Charge
	Protocol	OCPP1.6-J

Environment Requirements	Environment	Indoor and outdoor
	Enclosure Rating	NEMA Type 4
	IK Protection Rating	IK 10
	Storage Temperature	-40°F to 158°F (-40°C to 70°C)
	Operating Temperature	-22°F to 122°F (-30°C to 50°C)
	Operating Humidity (RH)	5% to 95%
	Altitude	≤ 2000 m (6561 ft)

Basic Information	Net Weight	Approximately 14.3 lbs (6.5 kg)
	Dimensions	335 x 226 x 141 mm
	Installation	Wall mounted
	Warranty	5 years

Compliance Information	Certification	UL2594, UL2251, UL2231-1, UL2231-2, UL1998, UL991, ENERGY STAR