




- SunRunner 90° Cable Clips are designed to mount at a 90° angle to the original SunRunner®.
- The SunRunner 90° will accommodate a single cable from .20" (5,1 mm) to .30" (7,6 mm); SunRunner 90-2 will accommodate (2) of these cables; SunRunner 4 will accommodate (4) of these cables.
- SunRunner 90° Series is designed for use with PV modules mounted in the "landscape" mode. PV modules with shorter than normal junction box cables cannot be dressed out to the sides of the module. The SunRunner 90° Series will also allow the junction box cables to be run to the adjacent modules across the short side of the PV module frame.
- · Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- DFARS Compliant.




HEYClip™ SunRunner® 90° Cable Clips


Double-Compression, Right Angle Design

C	PANEL THICKNESS CLAMPING RANGE Minimum Maximum in. mm. in. mm.			WIRE DIA. RANGE Maximum	PART NO.	DESCRIPTION	FOOTP Ax in.	HEIG		GHT	
Single Wire Clip for panels up to .125" (3,2 mm) thick											
.06	1,4	.13	3,2	.20" (5,1 mm)- .30" (7,6 mm) each cable	S6406	SunRunner® 90° Clip 100 Pack	.82 x .78	20,8 x 19,8	.39	9,9	
					S6446	SunRunner 90° Clip Bulk					
Double Wire Clip for panels up to .125" (3,2 mm) thick								NEW PRODUCTS			
.06	1,4	.13	3,2	.20" (5,1 mm)- .30" (7,6 mm) each cable	S6436	SunRunner® 90°-2 Clip 100 Pack	.65 x .98	16,5 x 24,9	.39	9,9	
					\$6476	SunRunner® 90°-2 Clip Bulk					
Four Wire Clip for panels up to .125" (3,2 mm) thick											
.06	1,4	.13	3,2	.20" (5,1 mm)- .30" (7,6 mm) each cable	\$6439	SunRunner® 90°-4 Clip 100 Pack	.56 x 1.61	14,2 x 40,9	.36	9,1	
					\$6479	SunRunner® 90°-4 Clip Bulk					





SunRunner® 90-2







Material

.020" thick heat treated 410 stainless steel (SunRunner 90-4)

.025" thick 304 stainless steel (SunRunner 90° and SunRunner 90-2)

Certifications

c(VL)us Certified by UL for Compliance with both Canadian and US Requirements

under File E54523 (SunRunner 90 only)