


Flat Tile Hook & Universal Tile Hook


The **Universal Tile Hook** is designed to work with Flat, S, and W shaped tile roofs which can typically install with minimal cutting/grinding of tiles. Provides enhanced install flexibility regardless of the rafter location due to the 1.25" vertical adjustability and 6" horizontal adjustability of the tile hook in relation to the large 4" x 8" base. Its 1/4" steel arm is thicker and more rigid compared to competing products on the market, requiring less roof attachments per installation. The **Flat Tile Hook** offers the most cost effective and efficient solution for mounting on flat concrete tile rooftops. Utilizing many of the same features as the Universal Tile Hook, the design focuses on maximizing speed and efficiency for installing specifically with concrete flat tiles.



The **Hanger Bolt Clamp** allows a versatile installation on roof surfaces that will not allow for L Feet or standoffs. These can be used with EJOT solar fastening systems.

Hanger Bolt Attachments	
Hanger Bolt	
Description	Item Code
Hanger Bolt Clamp	242-01102

**Standoffs** can be used on flat roofs or pitched roofs, comp shingle or tile and include a one-hole base, anodized standoff shaft, rubber rain collar and a standoff clamp assembly. The HD Standoffs are typically used on flat roofs with built up foam insulation where a taller standoff is required. They include a six-hole HD base, anodized HD standoff shaft, rubber rain collar and standoff clamp assembly. **Tilt Kits** can be used to tilt up arrays on low-slope roofs. The kits include two standoff mounts with base (one-hole for standard and six-hole for HD), anodized standoff shafts, rubber rain collars and the Standoff Clamp and L Foot Assembly.





Hanger Bolt Clamp



Standoff Kit, 5 1/2"



10° Tilt Kit w/ 5 ½" and 10" Standoffs



Standoff Clamp Assembly



Standoff Clamp and L Foot Assembly