

# Rail Specs- ProSolar® RoofTrac® Rail Technical Specifications

## Standard 1-1/2" Rail:

- Colors: Clear Anodized and Black Finish
- UL 2703 Listed
- Available in 136" and 168" lengths
- 1-1/2" Tall by 1-1/2" Wide
- 4 foot on center span
- Engineered and load tested to 45 lb/sq. ft. , equivalent of 125 mph wind speed per 2013 CBC / 2012 IBC / ASCE 7-10 to ensure safety and quality
- Sold in crates of 24 each or 60 each



## Deep 2-1/2" Rail:

- Colors: Clear Anodized and Black Finish
- UL 2703 Listed
- Available in 124", 136", and 168" lengths
- 2-1/2" Tall by 1-1/2" Wide
- 6 foot on center span
- Engineered and load tested to 45 lb/sq. ft. , equivalent of 125 mph wind speed per 2013 CBC / 2012 IBC / ASCE 7-10 to ensure safety and quality
- Sold in crates of 24 each and 60 each



## **XD 3" Rail:**

- Colors: Clear Anodized
- UL 2703 Listed
- Available in 136", 164", and 172" lengths
- 3" Tall by 1-1/2" Wide
- 8 foot on center span with SolarWedge®
- Engineered and load tested to 30 lb/sq. ft, equivalent of 110 mph wind speed per 2013 CBC/2012 IBC / ASCE 7-10
- Sold in crates of 24 each and 60 each

## **Related Links**

PV Mount Systems:

Attachments:

Accessories: