




# THE MOST DEPENDABLE SOLAR PRODUCT

## EAGLE® 72 G6B

570-590 WATT • N-TYPE BIFACIAL

Positive power tolerance of 0~+3%



- NYSE-listed since 2010, Bloomberg Tier 1 manufacturer
- Top performance in the strictest 3<sup>rd</sup> party labs
- Automated manufacturing utilizing artificial intelligence
- Vertically integrated, tight controls on quality
- Premium solar factories in USA, Vietnam, and Malaysia

### KEY FEATURES



#### N-Type Technology

N-type cells offer Jinko's in-house TOPCon technology with better performance and improved reliability.



#### Multi Busbar Half Cell Technology

Better light trapping and current collection to improve module power output and reliability.



#### Bifacial Power Gain

N-Type architecture increases bifaciality for higher backside bonus and better lifetime yield.



#### Low Temperature Coefficient

Best in class temperature coefficient for highest lifetime energy yield in all climates.



#### Industrial Grade Construction

Fire Type 29 with optimized dual-glass construction and thick frame for highest mechanical load resistance.



#### Shade Tolerant

Twin array design allows continued performance even with shading by trees or debris.



#### Protected Against All Environments

Certified to withstand humidity, heat, rain, marine environments, wind, hailstorms, and packed snow.




#### Warranty

12-year product and 30-year linear power warranty.

- ISO9001:2015 Quality Standards
- ISO14001:2015 Environmental Standards
- IEC61215, IEC61730 certified products
- ISO45001:2018 Occupational Health & Safety Standards
- UL61730 certified products



## ENGINEERING DRAWINGS



## MECHANICAL CHARACTERISTICS

No. of Half Cells	144 (2 x 72)
Dimensions	2278 x 1134 x 35mm (89.69 x 44.65 x 1.38in)
Weight	32kg (70.55lbs)
Front Glass	2.0mm, Anti-Reflection Coating
Back Glass	2.0mm, Heat Strengthened Glass
Frame	Anodized Aluminum Alloy
Junction Box	IP68 Rated
Output Cables	12 AWG, 1400mm (55.12in)
Fire Type	Type 29
Pressure Rating	5400Pa (Snow) & 2400Pa (Wind)


## TEMPERATURE CHARACTERISTICS

Temperature Coefficients of Pmax	-0.29%/°C
Temperature Coefficients of Voc	-0.25%/°C
Temperature Coefficients of Isc	0.045%/°C
Nominal Operating Cell Temperature (NOCT)	45±2°C
Bifacial Factor	80±5%

## MAXIMUM RATINGS

Operating Temperature (°C)	-40°C~+85°C
Maximum System Voltage	1500VDC
Maximum Series Fuse Rating	30A

## ELECTRICAL PERFORMANCE & TEMPERATURE DEPENDENCE



## PACKAGING CONFIGURATION

(Two pallets = One stack)  
31pcs/pallets, 62pcs/stack, 558pcs/40 HQ Container

## BIFACIAL OUTPUT-REAR SIDE POWER GAIN

	Maximum Power (Pmax)	604Wp	609Wp	614Wp	620Wp
5%	598Wp	23.17%	23.37%	23.57%	23.78%
15%	656Wp	25.38%	25.60%	25.82%	26.05%
25%	713Wp	27.59%	27.83%	28.06%	28.31%

## WARRANTY

12-year product and 30-year linear power warranty

1<sup>st</sup> year degradation not to exceed 1%, each subsequent year not to exceed 0.4%, minimum power at year 30 is 87.4% or greater.

## ELECTRICAL CHARACTERISTICS

Module Type	JKM570N-72HL4-BDV		JKM575N-72HL4-BDV		JKM580N-72HL4-BDV		JKM585N-72HL4-BDV		JKM590N-72HL4-BDV	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	570Wp	430Wp	575Wp	433Wp	580Wp	437Wp	585Wp	441Wp	590Wp	445Wp
Maximum Power Voltage (Vmp)	43.58V	40.56V	43.73V	40.73V	43.88V	40.89V	44.02V	41.05V	44.17V	41.21V
Maximum Power Current (Imp)	13.08A	10.59A	13.15A	10.64A	13.22A	10.69A	13.29A	10.74A	13.36A	10.79A
Open-circuit Voltage (Voc)	52.10V	49.49V	52.30V	49.68V	52.50V	49.87V	52.70V	50.06V	52.90V	50.25V
Short-circuit Current (Isc)	13.83A	11.16A	13.89A	11.21A	13.95A	11.26A	14.01A	11.31A	14.07A	11.36A
Module Efficiency STC (%)	22.07%		22.26%		22.45%		22.65%		22.84%	

\*STC: ☀ Irradiance 1000W/m<sup>2</sup>  
NOCT: ☀ Irradiance 800W/m<sup>2</sup>

🌡 Cell Temperature 25°C  
🌡 Ambient Temperature 20°C

☁ AM = 1.5  
☁ AM = 1.5  
🌀 Wind Speed 1m/s

\*Power measurement tolerance: ±3%

The company reserves the final right for explanation on any of the information presented hereby. JKM570-590N-72HL4-BDV-F35-F1-US

BUILDING YOUR TRUST IN SOLAR. [WWW.JINKOSOLAR.US](http://WWW.JINKOSOLAR.US)

**Jinko** Solar