

# 6 & 12 Batteries

## BOSS Cabinets



Certified to UL 9540  
and UL 9540A  
Fire Safety Tested



Expand your energy storage - with the **BOSS.6** and **BOSS.12**. These battery bank housings and wiring solutions with built-in shelving are carbon-steel and weather-resistant. The BOSS systems consolidate PHI or AmpliPHI™ battery banks that can be paired with any compatible Balance of System equipment to bring additional capacity. They include terminal blocks for electrical wiring in parallel, busbar-to-terminal block battery cabling, and terminal block to inverter cabling when ordered.

## FEATURES



### Temperature-Controlled Protection

Equipped with bus bars for easy wiring and corrosion-resistant fan prevents PHI batteries from reaching maximum 120°F charging temperature.



### Lithium Ferro Phosphate (LFP) Chemistry

Energized with safer, cobalt-free, lithium ion phosphate PHI and AmpliPHI batteries that outperform alternative solutions.



### Scalable For Any Energy Need

Designed to hold up to 6 (or 12) PHI or AmpliPHI batteries.



### Versatile Installation Options

NEMA 3R-rated, weather-resistant enclosures.



### Pairable Products

Can be paired with SimpliPHI 6 kW Inverter or AccESS.



### Certified for Safety

Certified to UL 9540 and UL 9540A  
Fire Safety Tested.

# 6&12 BOSS Cabinets

## Batteries



**BRIGGS&STRATTON**



Certified to UL 9540  
and UL 9540A  
Fire Safety Tested

BOSS.6 Specifications	
<b>Model Number</b>	BOSS.6 - 053003
<b>Dimensions</b>	36" W x 36"H (40" w/feet) x 16" D / 91.4 cm W x 91.4 cm H (101.6 cm w/feet) x 40.64 cm D
<b>Weight</b>	180 lbs (81.64kg.) w/o batteries
<b>Enclosure Rating</b>	NEMA 3R Outdoor Rated
<b>Mounting</b>	Free-standing or Pad-mounted
<b>Knockouts</b>	3 x Trade Size 1 Knockouts per side (6 total)
<b>Built-In DC Connections</b>	2 x 5-point Terminal Busbars, 3/8" lugs, 650 ADC
<b>Charging Temperature<sup>1</sup></b>	32°F to 120°F (0°C to 49°C)
<b>Maximum Contained Battery Quantity</b>	Six (6) AmpliPHI or PHI 3.8, 3.5 or 3.4 batteries (each battery measuring 13.5" W x 15.5" H w/terminals x 8" D)
<b>Enclosure Warranty Period</b>	2 years



Certified to UL 9540  
and UL 9540A  
Fire Safety Tested

BOSS.12 Specifications	
<b>Model Number</b>	BOSS.12 - 053002
<b>Dimensions</b>	29.5" W x 76"H (w/feet) x 20" D / 75 cm W x 193 cm H (w/feet) x 51 cm D
<b>Weight</b>	428 lbs (194.138 kg.) w/o batteries
<b>Enclosure Rating</b>	NEMA 3R Outdoor Rated
<b>Mounting</b>	Free-standing or Pad-mounted
<b>Built-In DC Connections</b>	2 x 5-point Terminal Busbars, 3/8" lugs, 650 ADC
<b>Charging Temperature<sup>1</sup></b>	32°F to 120°F (0°C to 49°C)
<b>Maximum Contained Battery Quantity</b>	Twelve (12) AmpliPHI or PHI 3.8, 3.5 or 3.4 batteries (each battery measuring 13.5" W x 15.5" H w/ terminals x 8" D)
<b>Enclosure Warranty Period</b>	2 years

<sup>1</sup> Max operating ranges. Refer to Installation Manual for recommended conditions.  
All specifications listed are typical/nominal and subject to change without notice.  
Engineered and Manufactured in California, USA

Briggs & Stratton has a policy of continuous product improvement and reserves the right to modify its specifications at any time and without prior notice. Please visit BRIGGSandSTRATTON.com for the latest information.  
BS1399 - 8/23

**BRIGGS & STRATTON**  
POST OFFICE BOX 702  
MILWAUKEE, WI 53201 USA