PWRCELL EX BATTERY MODULE



3.0kWh PWRcell EX Battery Module Model #: G0080001 Model #: G0080003

Build a better backup system with the Generac EX Battery Module for PWRcell™. Add capacity and backup power with as few as three or as many as six modules. Upgrade a PWRcell Battery post-installation with the addition of more EX modules for more power and capacity.

FEATURES & BENEFITS

- Suitable for in indoor and outdoor cabinets
- · Modular: Stack the right number of battery modules for the application
- · Upgradeable: Add more modules later when consumer needs change
- · Easy to install: At just 58.6lbs, installers won't need special equipment to move and install these batteries

SPECIFICATIONS	G0080001	G0080003
NOMINAL VOLTAGE:	43.2 VDC	44.4 VDC
USABLE CAPACITY @ TYPICAL VOLTAGE:	3.00 kWh	
MAXIMUM AMBIENT OPERATING TEMPERATURE RANGE:	14 to 122 °F (-10 to 50 °C)	
OPTIMAL AMBIENT OPERATING TEMPERATURE:	41 to 104 °F (5 to 40 °C)	
OPTIMAL STORAGE TEMPERATURE RANGE:	-4 to 77 °F (<6 mo)	
MAXIMUM STORAGE TEMPERATURE:	122 °F (<1 mo)	
SCALABILITY:	3-6 pcs in series	
DIMENSIONS, L x W x H - IN (MM):	17.3" x 17.7" x 3.5" (440 x 450 x 88)	
WEIGHT - LB (KG):	58.6 (26.6)	
BATTERY CHEMISTRY:	Lithium Nickel Manganese Cobalt (NMC)	
WARRANTY:	10 years or 7.56MWh Throughput (per module)	
COMPLIANCE:	UL 1973	

Note: Charge/discharge rate may be reduced at temperature extremes

Note: All EX battery models used in a PWRcell Battery Cabinet must be the same model. Do NOT combine G0080001 and G0080003 modules in a single battery cabinet

Generac Power Systems, Inc. S45 W29290 Hwy. 59, Waukesha, WI 53189

www.Generac.com | 888-GENERAC (436-3722)

A0000953960 REV C

©2021 Generac Power Systems. All rights reserved. Specifications are subject to change without notice.

