

<b>Device short name</b>	<b>Conext System Control Panel</b>
<b>Electrical specifications</b>	
Nominal voltage	15 VDC
Min. operating network voltage	14.25 VDC
Max. operating network voltage	15.75 VDC
Max. operating current at nominal voltage	200 mA
<b>General specifications</b>	
Dimensions (H x W x D)	15.2 x 10.3 x 4.0 cm (5.9 x 2.6 x 1.6 in)
Weight	200 g (0.4 lb)
Shipping weight	800 g (1.8 lb)
Mounting options	Panel-mount, wall-mount
IP rating / location	IP20, indoor only
Operating temperature range	-20 to 50°C (-4°F to 122°F)
Part number	865-1050-01
<b>Features</b>	
Network	Protocol: Xanbus / Connectors: RJ45
Internal clock	Provides network time
Memory	Non volatile
Alarm	Audible
Display	Backlit LCD. Green / red LED
Front-panel interface	Four menu buttons, One standby button
Warranty	2 to 5 years (depending on country)
<b>Regulatory approvals</b>	
Safety	CSA 107.1, UL 458 4 <sup>th</sup> Ed
EMC	CE directive 2004 / 108 / EC, IEC / EN61000-6-3, IEC / EN61000-6-1, FCC Part 15B Class B, Industry Canada ICES-00. Class B, C-Tick
<b>Included parts</b>	
	One remote head
	One network terminal
	One CAT5 cable (2.1 m)
	One mounting plate
	One mounting bracket
	Four #8 screws
	Two #6 screws

Specifications are subject to change without notice.

**Conext Automatic Generator Start works with the following Schneider Electric products**



**Conext XW inverter/charger**

XW 5548 NA Product no. 865-5548-01  
 XW 6848 NA Product no. 865-6848-01  
 XW 7048 E Product no. 865-7048-61  
 XW 8548 E Product no. 865-8548-61



**Conext SW inverter/charger**

SW 2524 120 Product no. 865-2024  
 SW 4024 120 Product no. 865-4024  
 SW 2524 230 Product no. 865-2524-61  
 SW 4024 230 Product no. 865-4024-61



**MPPT 60 150 solar charge controller**

Product no. 865-1030-1



**MPPT 80 600 solar charge controller**

Product no. 865-1032



**Conext Automatic Generator Start (AGS)**

Product no. 865-1060-01



**Conext Combox communication device**

Product no. 865-1058



**Conext Battery Monitor**

Product no. 865-1080-01