

Energy monitor and control, Schneider Energy Monitor, load disaggregation, Zigbee Ethernet POE

SEMONITOR

Main

Product or Component Type	Energy meter
Mobile App name	Schneider Home
Type of measurement	Energy consumption total
[Us] rated supply voltage	90132 V AC/DC
Network Frequency	50/60 Hz
maximum consumption	5 VA
Accuracy class	Class 2 UL 61010-1
Input type	Current transformer

Complementary

Colour tint	white
Communication Service	Active energy per usage
Measurement category	Category IV UL 61010-1
Height	1.3 in (32 mm)
Width	2.4 in (60 mm)
Depth	7.09 in (180 mm)
Net Weight	1.810 lb(US) (0.821 kg)
Range compatibility	current transformer

Environment

IP degree of protection	IPx0
Operating altitude	09842.52 ft (03000 m)

Ordering and shipping details

GTIN 3606487024484

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.26 in (3.2 cm)
Package 1 Width	2.60 in (6.6 cm)
Package 1 Length	7.13 in (18.1 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Weight

29.0 oz (821 g)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Under investigation	
California proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"	

Use Again

○ Repack and remanufacture		
Take-back	No	