

POWER UNINTERRUPTED

MAX HYBRID 15

With the Max Hybrid 15, you have the flexibility to configure up to 20 stackable batteries per inverter, allowing you to create a tailored power system that fits your energy requirements.







DURACELL



MAX HYBRID 15



15-30 Example Shown

Battery	15-15	15-20	15-25	15-30	15-40
Capacity	15 kWh	20 kWh	25 kWh	30 kWh	40kWh
# Of Stackable Modules	3	4	5	6	8
Grid to Battery Charge Efficiency			96%		

AC Output Power 15kW On-Grid &	Off-Grid		
Connections	120/240/208V Split Phase		
Continuous AC Power with PV	15,000W 62.5A-L (240V)		
Continuous AC Power from Batteries	12,000W 50A-L (240V)		
Total Harmonic Distortion (THD)	0.03		
Surge AC Power 10sec	24,000VA L-L (240V)		
Surge AC Power 100ms	30,000VA L-L (240V)		
Fault Current 5sec	94A w/PV 75A w/o		
Fault Current 100ms	PV 120A		
Parallel Stacking	Yes - Up to 12		
Frequency	60/50Hz		
Continuous AC Power with Grid or	48,000W 200A L-L (240V)		
Generator	24,000W 200A L-N (120V)		
CEC Efficiency	96.5% (Peak 97.5%)		
Idle Consumption Typical-No Load	90W		
Sell Back Power Modes	Limited to Household/		
	Fully Grid-Tied		
Design (DC to AC)	Transformerless DC		
Response Time (Grid-Tied to O -Grid)	Sms		
Power Factor	+/-0.9-1.0		

Experience uninterrupted power with Duracell Power Center's Max Hybrid 15 inverter. Designed for residential and commercial use, this advanced inverter provides seamless electricity flow during outages.

With a 15,000-watt capacity, it powers multiple appliances simultaneously. The hybrid functionality intelligently switches between grid power and battery power for maximum efficiency and reduced costs. Safety features protect your devices from overload and short-circuits. Its sleek design and easy installation make it an ideal choice.

Trust Duracell for reliable performance and peace of mind in powering your world.

Protections and Certifications		
Electronics Certified Safety by SGS Labs	Yes	
to NEC & UL Specs - NEC 690.48 & NEC 705.4/6		
Grid Sell Back-UL1741-2010/2018, IEEE1547a	Yes	
-2003/2014, FCC 15 Class B, UL1741SB,	Integrated	
CA Rule 21, HECO Rule 14H		
PV DC Disconnect Switch NEC 240.15	Integrated	
Ground Fault Detection - NEC 690.5	Integrated	
PV Arc Fault Detection - NEC 690.11	Integrated	
PV Input Lightning Protection	Integrated	
24,000W 200A L-N (120V) 96.5%	Integrated	
(Peak 97.5%) 90W		
PV String Input Reverse Polarity Protection	Integrated	
AC Output Breakers - 200A	Integrated	
200A x 2 Battery Breaker/Disconnect	DC Type II/AC	
Limited to Household/Fully Grid-Tied	Туре II	
Surge Protection		

Solar	
Max Allowed PV Power	19,500W
Max PV Power Delivered to Battery & AC Outputs	15,000W
Max DC Voltage (Voc)	500V @ 26A
MPPT Voltage Range	125-425V
Starting Voltage	125V
Number of MPPT	3
Max Solar Strings Per MPPT	2
Max DC Current per MPPT (Self Limiting)	26A
Max AC Coupled Input (Micro/String Inverters)	19,200W