

## MS-US Series

5-11.4kW | Single Phase  
Up to 3 MPPTs

The MS-US Series is a high-quality PV solution engineered to meet the demanding needs of U.S. homeowners. Allowing a maximum 16A input current per string and supporting up to 160% DC oversizing, this product was created for long-term, trouble-free lifetime operation with maximum energy production. Built-in optimization effortlessly addresses complex rooftops and shaded areas without the need for traditional module-level optimizers, which add cost and complexity to the system.



### Smart Control & Monitoring

- Power export limit
- 24-hour load consumption monitoring



### Superb Safety & Reliability

- Integrated AFCI & Rapid Shutdown
- Optional DC Type II SPD & SPD failure alarm



### Fully Integrated Design

- Optimization built-in
- High quality, robust components



### High Power Generation

- Up to 16A max. DC input current per string
- Up to 160% DC input oversizing

Technical Data		GW5000-MS-US30	GW6000-MS-US30	GW7600-MS-US30	GW7700-MS-US30	GW9600-MS-US30	GW11K4-MS-US30
<b>Input</b>							
Max. Input Voltage (V)		600					
MPPT Operating Voltage Range (V)		65 ~ 550					
Start-up Voltage (V)		80					
Nominal Input Voltage (V) (at 240V)		380					
Nominal Input Voltage (V) (at 208V)		330					
Max. Input Current per MPPT (A)		16					
Max. Short Circuit Current per MPPT (A)		23.4					
Number of MPP Trackers		2	2	2	3	3	3
Number of Strings per MPPT		1					
<b>Output</b>							
Nominal Output Power (W) (at 240V)		5000	6000	7600	7680	9600	11400
Nominal Output Power (W) (at 208V)		4333	5200	6580	6650	8320	9880
Nominal Output Apparent Power (VA) (at 240V)		5000	6000	7600	7680	9600	11400
Nominal Output Apparent Power (VA) (at 208V)		4333	5200	6580	6650	8320	9880
Max. AC Active Power (W) (at 240V)		5000	6000	7600	7680	9600	11400
Max. AC Active Power (W) (at 208V)		4333	5200	6580	6650	8320	9880
Max. AC Apparent Power (VA) (at 240V)		5000	6000	7600	7680	9600	11400
Max. AC Apparent Power (VA) (at 208V)		4333	5200	6580	6650	8320	9880
Nominal Output Voltage (V)		240 / 208					
Nominal AC Grid Frequency (Hz)		60					
Max. Output Current (A)		20.8	25.0	31.7	32.0	40.0	47.5
Power Factor		~1 (Adjustable from 0.8 leading to 0.8 lagging)					
Max. Total Harmonic Distortion		<3%					
<b>Efficiency</b>							
Max. Efficiency		97.5%	97.5%	97.5%	97.5%	97.8%	97.8%
CEC Efficiency (at 240V)		96.5%	96.5%	96.5%	96.5%	97.0%	97.0%
CEC Efficiency (at 208V)		96.0%	96.0%	96.5%	96.5%	96.5%	96.5%
<b>Protection</b>							
PV String Current Monitoring		Integrated					
PV InsulationResistance Detection		Integrated					
Residual Current Monitoring		Integrated					
PV Reverse Polarity Protection		Integrated					
Anti-islanding Protection		Integrated					
AC Overcurrent Protection		Integrated					
AC Short Circuit Protection		Integrated					
AC Overvoltage Protection		Integrated					
DC Switch		Integrated					
DC Surge Protection		Type III (Type II Optional)					
AC Surge Protection		Type III (Type II Optional)					
AFCI		Integrated					
Rapid Shutdown		Integrated					
<b>General Data</b>							
Operating Temperature Range (°F)		-13 ~ 140 (-25 ~ 60°C)					
Derating temperature (°F)		113 (45°C)					
Storage Temperature Range (°F)		-40 ~ +158 (-40 ~ +70°C)					
Relative Humidity		0 ~ 95%					
Max. Operating Altitude (ft)		9842 (3000m)					
Cooling Method		Natural Convection					
User Interface		LED, WLAN + APP					
Communication		RS485, WiFi or Bluetooth or 4G or LAN (Optional)					
CommunicationProtocols		Modbus-RTU (SunSpec Compliant)					
Weight (lb)		51.8 (23.0kg)	51.8 (23.0kg)	51.8 (23.0kg)	55.1 (25.0kg)	55.1 (25kg)	55.1 (25kg)
Dimension(W × H × D in)		19.2 × 26.4 × 7.8 (487 × 670 × 199 mm)					
Noise Emission(dB)		<25	<25	<25	<35	<35	<35
Topology		Non-isolated					
Self-consumptionat Night (W)		<5					
Ingress ProtectionRating		Type 4X (IP66)					

\*: Please visit GoodWe website for the latest certificates.