




YUKON N Series

Half-Cell N-Type Bifacial Module

575-590Wp
Module Power Output

22.84%
Max Efficiency



Key Features



High module conversion efficiency



Better temperature coefficient



Super multi busbar technology



Low attenuation long warranty



Superior load capacity



Higher bifaciality




USA based liability insurance



Houston, Texas based company

Warranty



15 Years
Guarantee on product material and workmanship

30 Years
Linear power output warranty

Product Certification

IEC61215; IEC61730; UL61215; UL61730

IEC62804

PID

IEC61701

Salt Mist

IEC62716

Ammonia Resistance

IEC60068

Dust and Sand

IEC61215

Hailstone

Fire Type (UL61730): Type 29

ISO14001:2015; ISO9001:2015; ISO45001:2018



CALIFORNIA ENERGY COMMISSION



About SEG Solar

Founded in 2016, SEG is a leading vertically integrated PV manufacturer headquartered in Houston, Texas, U.S., and is dedicated to delivering reliable and cost-effective solar modules to the utility, commercial and residential markets. By the end of 2023, SEG has shipped over 5 GW of solar modules worldwide. The company is expected to exceed a production capacity of 5.5 GW by the end of 2024.



Download Datasheet

Electrical Characteristics

Module Type	SEG-575-BTA-BG			SEG-580-BTA-BG			SEG-585-BTA-BG			SEG-590-BTA-BG		
	Front STC	Front NOCT	Back STC	Front STC	Front NOCT	Back STC	Front STC	Front NOCT	Back STC	Front STC	Front NOCT	Back STC
Maximum Power -Pmp(Wp)*	575	433	460	580	437	464	585	441	468	590	445	472
Open Circuit Voltage -Voc(V)	51.73	50.01	51.71	51.95	50.29	51.93	52.16	50.56	52.14	52.37	50.79	52.35
Short Circuit Current -Isc(A)	13.79	11.04	11.04	13.84	11.08	11.08	13.89	11.12	11.12	13.94	11.17	11.17
Maximum Power Voltage -Vmp(V)	43.82	41.24	43.80	44.02	41.42	44.00	44.22	41.64	44.20	44.43	41.86	44.41
Maximum Power Current -Imp(A)	13.12	10.50	10.50	13.17	10.55	10.55	13.23	10.59	10.59	13.28	10.63	10.63
Module Efficiency(%)	22.26			22.45			22.65			22.84		
Power Tolerance(W)							(0, +4.99)					
Maximum System Voltage							1500V DC					
Maximum Series Fuse Rating							30 A					
Bifaciality							80±10%					

STC: Irradiance 1000 W/m² module temperature 25°C AM=1.5

NOCT: Irradiance 800W/m² ambient temperature 20°C module temperature 45°C wind speed: 1m/s




*Measuring tolerance: ±3%

Mechanical Specifications

External Dimension	2278 x 1134 x 35 mm
Weight	32.7 kg
Solar Cells	N-Type Mono 144 pcs(72 x 2)
Front Glass	2.0 mm AR coating semi-tempered glass
Back Glass	2.0 mm Semi-tempered glass
Frame	Anodized aluminium alloy
Junction Box	IP68 / 3 diodes
Connector Type	MC4
Cable Type	12 AWG PV Wire(UL)
Cable Length	Portrait: 400 mm(+) / 200 mm(-)
Mechanical Load(Front)	5400 Pa / 113 psf*
Mechanical Load(Rear)	2400 Pa / 50 psf*

*Refer to SEG installation manual for details

Technical Drawing



*Refer to SEG installation manual for details

Temperature Characteristics **Packing Configuration**

Pmax Temperature Coefficient	-0.30 %/°C
Voc Temperature Coefficient	-0.25 %/°C
Isc Temperature Coefficient	+0.046 %/°C
Operating Temperature	-40~+85 °C
Nominal Operating Cell Temperature (NOCT)	45±2 °C

Container*	20'GP	40'HQ	40'HQ (For USA)
Pieces per Pallet	31	31	31
Pallets per Container	4	20	18
Pieces per Container	124	620	558

*Refer to the SEG container technical documentation for 53' box trailer or other trucks loading quantity

Curves of PV Module

