



YUKON N Series


Half-Cell N-Type Bifacial Module

625-640W_p

Module Power Output

22.90%

Max Efficiency



Key Features



High module conversion efficiency



Better temperature coefficient



Super multi busbar technology



Low attenuation long warranty



Superior load capacity



Higher bifaciality




USA based liability insurance



Houston, Texas based company

Warranty



15
Years

Guarantee on product material and workmanship

30
Years

Linear power output warranty

Product Certification

IEC61215; IEC61730; UL61215; UL61730

IEC62804

PID

IEC61701

Salt Mist

IEC62716

Ammonia Resistance

IEC60068

Dust and Sand

IEC61215

Hailstone

Fire Type (UL61730): Type 29

ISO14001:2015; ISO9001:2015; ISO45001:2018



CALIFORNIA ENERGY COMMISSION



Download Datasheet

About SEG Solar

Founded in 2016, SEG is a leading vertically integrated PV manufacturer headquartered in Houston, Texas, U.S., and is dedicated to delivering reliable and cost-effective solar modules to the utility, commercial and residential markets. By the end of 2023, SEG has shipped over 5 GW of solar modules worldwide. The company is expected to exceed a production capacity of 5.5 GW by the end of 2024.

Electrical Characteristics

Module Type	SEG-625-BTZ-BG			SEG-630-BTZ-BG			SEG-635-BTZ-BG			SEG-640-BTZ-BG		
	Front STC	Front NOCT	Back STC	Front STC	Front NOCT	Back STC	Front STC	Front NOCT	Back STC	Front STC	Front NOCT	Back STC
Maximum Power -Pmp(Wp)*	625	471	500	630	475	504	635	479	508	640	483	512
Open Circuit Voltage -Voc(V)	56.95	54.10	56.93	57.08	54.22	57.06	57.21	54.34	57.19	57.34	54.46	57.32
Short Circuit Current -Isc(A)	13.80	11.14	11.04	13.86	11.19	11.09	13.92	11.24	11.14	13.98	11.29	11.19
Maximum Power Voltage -Vmp(V)	47.54	44.69	47.52	47.70	44.83	47.68	47.86	45.02	47.84	48.02	45.18	48.00
Maximum Power Current -Imp(A)	13.15	10.54	10.52	13.21	10.59	10.57	13.27	10.64	10.62	13.33	10.69	10.67
Module Efficiency(%)	22.36			22.54			22.72			22.90		
Power Tolerance(W)						(0, +4.99)						
Maximum System Voltage						1500V DC						
Maximum Series Fuse Rating						30 A						
Bifaciality						80±10%						

STC: Irradiance 1000 W/m² module temperature 25°C AM=1.5

NOCT: Irradiance 800W/m² ambient temperature 20°C module temperature 45°C wind speed: 1m/s



*Measuring tolerance: ±3%

Mechanical Specifications

External Dimension	2465 x 1134 x 30 mm
Weight	34.0 kg
Solar Cells	N-Type Mono 156 pcs(78 x 2)
Front Glass	2.0 mm AR coating semi-tempered glass
Back Glass	2.0 mm Semi-tempered glass
Frame	Anodized aluminium alloy
Junction Box	IP68 / 3 diodes
Connector Type	PV-C002-xy or MC4
Cable Type	12 AWG PV Wire(UL)
Cable Length	Portrait: 400 mm(+) / 200 mm(-) Landscape: 1200 mm(+) / 1200 mm(-) or customized length
Mechanical Load(Front)	5400 Pa / 113 psf*
Mechanical Load(Rear)	2400 Pa / 50 psf*

*Refer to SEG installation manual for details

Technical Drawing



Temperature Characteristics


Pmax Temperature Coefficient	-0.30 %/°C
Voc Temperature Coefficient	-0.25 %/°C
Isc Temperature Coefficient	+0.046 %/°C
Operating Temperature	-40~+85 °C
Nominal Operating Cell Temperature (NOCT)	45±2 °C

Packing Configuration

Container*	20'GP	40'HQ
Pieces per Pallet	36	36
Pallets per Container	4	16
Pieces per Container	144	576

*Refer to the SEG container technical documentation for 53' box trailer or other trucks loading quantity

Curves of PV Module



*Refer to SEG installation manual for details