




LiFePOWER4 24V

200AH BATTERY

Built-In BMS 100A

Storage Capacity 5.12 kWh

5 Year Warranty



Our EG4 LiFePOWER4 batteries offer second to none price to performance. Get peace of mind knowing these batteries are designed to last for more than 7000 deep charge and discharge cycles; beyond 15 years with an 80% depth of discharge daily!

PC Monitoring Software

See real-time statistics of your battery.

Parallel up to 16 Batteries

Get the most power possible! Up to 81.9 kWh while maintaining BMS communications.

Built-In Circuit Breaker

For added safety.


Welded Prismatic Cell Connections

Never worry about losing power due to a loose internal connection.

Rack-Mount Design

4U server rack mounting makes it convenient to store.

Closed loop communications with Growatt 24V inverters.





LIFEPOWER₄ 24V

200AH BATTERY

Nominal Operating Parameters			
Voltage	25.6V		
Capacity	200Ah		
Charging Voltage (Bulk/Absorb)	28.1V (+/- 0.2V)		
Float	27V (+/- 0.2V)		
Low DC Cutoff	23.5-22V (depending on load - start high, lower if needed)		
Charging Current	Max Constant Charge: 100A (30-50A recommended)		
Discharging Current	Max Constant Discharge: 100A		
Environmental Parameters			
Charging Range	32°F to 122°F (0°C to 50°C)		
Discharging Range	-4°F to 131°F (-20°C to 55°C)		
Storage Range (Optimal)	32°F to 113°F (0°C to 45°C)		
Altitude	<9843 ft. (3000m)		
BMS Parameters			
Charge	Spec	Delay	Recovery
Cell Voltage Protection	3.65V	1 sec	3.6V
Module Voltage Protection	29.2V	1 sec	28.8V
Over Charging Current 1	>100A	20 sec	
Over Charging Current 2	≥120A	2 sec	
Temperature Protection	<32°F or >131°F (<0°C or >55°C)	1 sec	
Discharge			
Cell Voltage Protection	2.5V	1 sec	2.7V
Module Voltage Protection	20.0V	1 sec	21.6V
Over Charging Current 1	>100A	10 sec	60 sec
Over Charging Current 2	>150A	3 sec	60 sec
Short-Circuit	>250A	1 sec	
Temperature Protection	<-4°F or >140°F (<-20°C or >60°C)	1 sec	
BMS	Parameter		Condition
PCB Temperature Protection	>203°F (>95°C)	Delay 1 sec	Recovery @ <167°F (<75°C)
Cell Balance	100mA	Passive Balance	Cell Voltage Difference >40mV
Temperature Accuracy	3%	Cycle Measurement	Measuring Range -40 to 100°C
Voltage Accuracy	0.5%	Cycle Measurement	For Cells & Module
Current Accuracy	3%	Cycle Measurement	Measuring Range -200 to +200
SOC	5%		Integral Calculation
Power Consumption - Sleep/Off Mode	<300uA	Delay 1 sec	Storage/Transport
Power Consumption - Operating Mode	<14mA		Charging/Discharging
Communication Ports	RS485		

